THE CDF II DETECTOR

TECHNICAL DESIGN REPORT

FERMILAB-Pub-96/390-E

The CDF II Collaboration

October 1996

Contents

1 Overview **1-1**
1.1 Introduction . . . 1-1
1.2 History . . . 1-1
1.3 Design Parameters . . . 1-2
1.3.1 Accelerator Configuration . . . 1-2
1.3.2 Physics Performance Requirements . . . 1-2
1.4 The CDF II Detector . . . 1-3
1.4.1 Tracking Systems . . . 1-3
1.4.2 Calorimeter Systems . . . 1-8
1.4.3 Muon Systems . . . 1-9
1.4.4 Electronics and Triggering . . . 1-11
1.5 The CDF II Upgrade Plan . . . 1-13
1.5.1 Outlook . . . 1-13

2 Physics Goals **2-1**
2.1 Overview . . . 2-1
2.1.1 Summary of CDF II Physics . . . 2-1
2.1.2 Physics and Detector . . . 2-3
2.1.3 Detailed Discussion . . . 2-3
2.2 Properties of the Top Quark . . . 2-4
2.2.1 Review of Run I Analysis . . . 2-4
2.2.2 Lessons from Run I . . . 2-9
2.2.3 Impact of Upgrades on Top Physics . . . 2-9
2.2.4 Event Yield . . . 2-10
2.2.5 Measurement of the Top Quark Mass . . . 2-10
2.2.6 Production Cross Section, $\sigma_{t\bar{t}}$ . . . 2-11
2.2.7 Measurement of a t $\rightarrow$ b Branching Fraction and a Lower Limit on V_{tb} . . . 2-12
2.2.8 Search for Anomalously Large Rare Decays . . . 2-14
2.2.9 Summary of Top Physics . . . 2-15
2.3 Precision Electroweak Program . . . 2-19
2.3.1 Introduction . . . 2-19
2.3.2 Event Yields . . . 2-19
2.3.3 W Mass . . . 2-23
2.3.4 W Width . . . 2-28
2.3.5 Gauge Boson Couplings . . . 2-28
2.3.6 Forward-Backward Z Asymmetry . . . 2-32
2.3.7 PDF Measurements and Issues . . . 2-34
2.4 Search for New Phenomena . . . 2-38
2.4.1 Introduction . . . 2-38

2.4.2 Supersymmetry . . . 2-39
2.4.3 New Gauge Bosons Z' and W' . . . 2-43
2.4.4 New Particles decaying to Dijets . . . 2-46
2.4.5 Topcolor Theory and the b-tagged Dijet Search . . . 2-46
2.4.6 Leptoquarks . . . 2-47
2.4.7 Compositeness . . . 2-48
2.4.8 Massive Stable Particles . . . 2-49
2.4.9 Technicolor . . . 2-50
2.4.10 Charged Higgs Search . . . 2-50
2.4.11 Summary . . . 2-51
2.5 Precision QCD at Large Q^2 . . . 2-55
2.5.1 Jet Cross Section . . . 2-55
2.5.2 Multijet Events . . . 2-58
2.5.3 Direct Photons . . . 2-59
2.5.4 W and Z boson production . . . 2-59
2.5.5 The extraction of α_S and the parton densities . . . 2-62
2.5.6 Summary of the benefits of Tevatron Run II to QCD studies . . . 2-63
2.6 Constraining the CKM Matrix . . . 2-66
2.6.1 Introduction . . . 2-66
2.6.2 The current CDF b program . . . 2-66
2.6.3 CDF II strategy for b physics . . . 2-67
2.6.4 CP Violation in the B system . . . 2-71
2.6.5 Determination of $|V_{td}/V_{ts}|$ . . . 2-78
2.6.6 B_c and Cabibbo suppressed decays . . . 2-83
2.6.7 Rare B decays . . . 2-83
2.6.8 Concluding remarks . . . 2-85

3 Overview of Tracking **3-1**
3.1 History and Capability . . . 3-1
3.2 Run I Tracking Strategy, and Shortcomings of the System . . . 3-2
3.3 Overview of the proposed system . . . 3-3

4 Central Outer Tracker (COT) **4-1**
4.1 Overview . . . 4-1
4.2 Mechanical . . . 4-2
4.2.1 End Plates . . . 4-2
4.2.2 Field Panels . . . 4-7
4.2.3 Shaper Panel . . . 4-8
4.2.4 Wires . . . 4-8
4.3 Material Count and Radiation Lengths . . . 4-8
4.4 Electrostatics and High Voltage . . . 4-9
4.4.1 Currents (Voltage sags and space charge distortions) . . . 4-9
4.4.2 High Voltage System . . . 4-10
4.4.3 Electrostatics . . . 4-10
4.5 Gas System and Wire Ageing . . . 4-11
4.5.1 CTC Wire ageing CTC in Ar-Et . . . 4-11
4.5.2 COT Wire Ageing in Ar-Et-CF_4. . . . 4-11
4.6 Readout Electronics and Trigger . . . 4-12
4.6.1 Front End . . . 4-13
4.6.2 ASD . . . 4-14

4.6.3 TDC . . . 4-15
4.6.4 DAQ . . . 4-15
4.6.5 Trigger . . . 4-15
4.6.6 Calibration . . . 4-16
4.6.7 Cooling . . . 4-16
4.7 Chamber Performance . . . 4-16
4.7.1 Position Resolution . . . 4-16
4.7.2 Two-track Resolution . . . 4-17
4.7.3 Luminosity Scaling . . . 4-19

5 Silicon Vertex Detector (SVX II) 5-1
5.1 Introduction . . . 5-1
5.2 Silicon Crystals . . . 5-5
5.2.1 Silicon Detector Layout . . . 5-5
5.2.2 The 90° stereo sensors . . . 5-6
5.2.3 Small Angle Stereo Detectors . . . 5-8
5.2.4 Silicon Detector Tests . . . 5-8
5.2.5 Radiation Issues . . . 5-10
5.3 Mechanical Design . . . 5-14
5.3.1 Ladder Design . . . 5-14
5.3.2 SVX II Readout Hybrid . . . 5-15
5.3.3 Ladder Cabling . . . 5-18
5.3.4 Bulkhead . . . 5-18
5.3.5 Spaceframe Specifications . . . 5-19
5.3.6 Cooling and Gas Systems . . . 5-21
5.4 SVX II Frontend Electronics . . . 5-23
5.4.1 The SVX3 Readout Chips . . . 5-23
5.4.2 SVX 3 Port Card . . . 5-26
5.5 SVX Data Acquisition . . . 5-27
5.5.1 Dense Optical Interface Module . . . 5-27
5.5.2 Fiber Interface Board (FIB) . . . 5-29
5.5.3 High Speed Fiber Link . . . 5-30
5.5.4 VRB and VRB Fanout Modules . . . 5-31
5.5.5 The SRC . . . 5-32
5.5.6 Readout into Level 3 . . . 5-34
5.6 SVX II Power Supplies . . . 5-35
5.7 SVX II Alarms and Limits System . . . 5-36
5.8 SVX II Performance Issues . . . 5-37
5.8.1 Hit Occupancies in the SVX II . . . 5-37
5.9 Operating the SVX II . . . 5-37
5.9.1 Calibration . . . 5-37
5.9.2 Beam Steering and Feedback Control . . . 5-37

6 Intermediate Silicon Layers (ISL) 6-1
6.1 Introduction . . . 6-1
6.2 Detector Design . . . 6-1
6.2.1 Comparison to SVX II . . . 6-1
6.2.2 Geometry . . . 6-2
6.2.3 Silicon Crystals . . . 6-2
6.2.4 Ladders . . . 6-2

6.2.5 Bulkheads . . . 6-4
6.2.6 ISL mechanical support . . . 6-4
6.3 Readout and Data Acquisition . . . 6-7
6.4 ISL Performance Issues . . . 6-8
6.4.1 Hit Occupancy . . . 6-8
6.4.2 Signal to Noise . . . 6-8
6.4.3 Material . . . 6-8
6.4.4 Hit resolution . . . 6-8
6.4.5 Acceptance . . . 6-8
6.5 Construction Tolerances . . . 6-9

7 Simulated Performance of Integrated Tracking System 7-1
7.1 Introduction . . . 7-1
7.2 Simulation of COT, ISL and SVX II . . . 7-1
7.3 Data Sample . . . 7-1
7.4 COT performance . . . 7-2
7.4.1 Projected COT performance based on CTC data . . . 7-2
7.4.2 Pattern Recognition in COT . . . 7-2
7.4.3 COT Simulation Results . . . 7-3
7.5 SVX II+ISL performance . . . 7-5
7.5.1 r-ϕ Tracking . . . 7-5
7.5.2 r-z Tracking . . . 7-6
7.5.3 Resolution of SVX II+ISL System . . . 7-7
7.5.4 b-tagging for $|\eta| > 1$ . . . 7-8
7.5.5 Pointing into COT . . . 7-8
7.6 Integrated Tracking Performance (SVX II+ISL+COT) . . . 7-8
7.6.1 Linking COT with SVX II+ISL: r-ϕ . . . 7-9
7.6.2 Linking COT with SVX II+ISL: r-z . . . 7-10
7.6.3 COT+SVX II+ISL Resolution . . . 7-11
7.6.4 Conclusions . . . 7-11

8 Central Calorimeter 8-1
8.1 Introduction . . . 8-1
8.2 Central E–M Calorimeter . . . 8-1
8.3 Central and Endwall Hadron Calorimeters . . . 8-4

9 Plug Upgrade Calorimeter 9-1
9.1 Overview . . . 9-1
9.2 Specification of Transverse Segmentation . . . 9-3
9.3 EM Calorimeter . . . 9-3
9.3.1 Design Specification . . . 9-3
9.3.2 Mechanical Design . . . 9-4
9.3.3 Detector Description . . . 9-4
9.3.4 EM Fiber Assembly Quality Control . . . 9-6
9.3.5 EM Tile/Fiber Assembly Quality Control . . . 9-7
9.4 Shower Maximum Detector . . . 9-8
9.4.1 Design Specification . . . 9-8
9.4.2 Detector Description . . . 9-8
9.4.3 SMD Fiber Assembly Quality Control . . . 9-9
9.4.4 SMD Scintillator Strips and Megastrips Quality Control . . . 9-9

9.5 Hadron Calorimeter . . . 9-10
9.5.1 Design Specification . . . 9-10
9.5.2 Mechanical Design . . . 9-11
9.5.3 Hadron Pizza Pan Assembly . . . 9-12
9.5.4 Hadron Fiber Assembly Quality Control . . . 9-13
9.5.5 Hadron Tile/Fiber Assembly Quality Control . . . 9-13
9.6 Optical System . . . 9-15
9.6.1 Optical Fibers . . . 9-15
9.6.2 Photomultipliers . . . 9-19
9.7 Stability Monitor . . . 9-25
9.7.1 Design Criteria . . . 9-25
9.7.2 Description of the Laser Light Distribution System . . . 9-26
9.8 Calibration Scheme . . . 9-27
9.8.1 Calorimeter Calibration . . . 9-27
9.8.2 Moving Radioactive Sources . . . 9-28
9.9 Test Stands . . . 9-29
9.9.1 Test Beam Module . . . 9-29
9.9.2 Cosmic Ray Test Stand . . . 9-29
9.10 Engineering Prototype Tests . . . 9-30
9.10.1 The Engineering Prototype . . . 9-30
9.10.2 Test Beam Studies . . . 9-31
9.10.3 Engineering Prototype Lessons . . . 9-33

10 Muon Detectors **10-1**
10.1 Central Muon Detector . . . 10-2
10.2 Central Muon Upgrade . . . 10-2
10.3 Central Muon Extension . . . 10-3
10.4 Muon Detector Upgrades for Run II . . . 10-4
10.4.1 Completion of the Central Muon Upgrade and Upgrade Scintillator . . . 10-4
10.4.2 Completion of the Central Muon Extension and Extension Scintillator . . . 10-7
10.5 Front-End Electronics . . . 10-8
10.5.1 Changes in the Central Muon Upgrade Front-End Electronics . . . 10-11
10.5.2 Changes in the Central Muon Upgrade Front-End Electronics . . . 10-12
10.6 Intermediate Muon Detection . . . 10-12
10.6.1 Overview . . . 10-12
10.6.2 Toroid Modifications . . . 10-12
10.6.3 IMU Barrel Chambers and Counters . . . 10-13
10.6.4 IMU Toroid Counters . . . 10-13
10.6.5 IMU Endwall Counters . . . 10-14
10.6.6 Triggering on $\eta \geq 1$ Muons . . . 10-14
10.6.7 Summary . . . 10-15
10.7 Performance: Extrapolation From Run I . . . 10-15

11 Front-End Electronics and DAQ **11-1**
11.1 Overview . . . 11-1
11.2 Calorimeter Front-End . . . 11-2
11.2.1 Calorimeter ADC: The QIE . . . 11-2
11.2.2 Shower-max detectors and preradiators . . . 11-4
11.2.3 Calorimeter TDC's . . . 11-5
11.3 Pipelined TDCs . . . 11-6

11.4 Muon-Detector TDCs . . . 11-7
11.5 Silicon Front-End Electronics . . . 11-7
11.6 Data Acquisition System . . . 11-8
11.6.1 Overview . . . 11-8
11.6.2 Front-End Crates and Controllers . . . 11-8
11.6.3 Trigger System Interface . . . 11-10
11.6.4 Master Clock . . . 11-11
11.6.5 Event Building Network . . . 11-11
11.6.6 Network Switch . . . 11-12
11.6.7 Level 3 Trigger . . . 11-13
11.6.8 Data Logging . . . 11-14
11.6.9 Partitioning . . . 11-15
11.7 Online Computing System . . . 11-15
11.7.1 Run Control . . . 11-15
11.7.2 Event Monitoring . . . 11-17
11.7.3 Hardware Configuration . . . 11-17
11.7.4 CDF ALARMS . . . 11-18

12 Trigger **12-1**
12.1 Overview . . . 12-1
12.2 Level 1 Trigger hardware . . . 12-2
12.2.1 Level 1 calorimeter hardware (L1CAL) . . . 12-3
12.3 The eXtremely Fast Tracker (XFT) . . . 12-5
12.3.1 Algorithm Description . . . 12-6
12.3.2 Algorithm Simulation . . . 12-7
12.3.3 Algorithm Implementation . . . 12-9
12.3.4 The Extrapolation Unit (XTRP) . . . 12-10
12.3.5 Level-1 Muon Trigger (L1 MUON) . . . 12-11
12.3.6 Global Level-1 . . . 12-12
12.4 Level 2 Trigger Hardware . . . 12-14
12.4.1 Level-2 Cluster Finder (L2CAL) . . . 12-15
12.4.2 Level-2 Shower Maximum Data Used in the Trigger . . . 12-15
12.4.3 Silicon Vertex Tracker (SVT) . . . 12-17
12.4.4 Level-2 Decision Hardware (Global Level 2) . . . 12-20
12.5 Trigger Rates . . . 12-22

13 Computing and Software **13-1**
13.1 The Run I System . . . 13-1
13.2 Expected Data Volume and processing requirements . . . 13-2
13.3 Computing Model . . . 13-3
13.3.1 Run I Computing Model . . . 13-3
13.3.2 The Run II Computing Model . . . 13-3
13.4 Software environment . . . 13-5
13.4.1 Software Methodology and Languages . . . 13-5
13.4.2 Code Mangement and Distribution . . . 13-5
13.4.3 Reconstruction and Analysis Framework . . . 13-6
13.5 Event Reconstruction . . . 13-6
13.6 Calibration Database . . . 13-7
13.7 Simulation . . . 13-7

14 Experimental Facilities **14-1**
14.1 Solenoid and Cryogenics 14-1
14.1.1 Lifetime 14-1
14.1.2 Necessary Repairs 14-2
14.1.3 Controls upgrade 14-2
14.2 Beam Pipe 14-2
14.3 Tevatron Monitor 14-3
14.4 Tevatron Shielding 14-4
14.4.1 Shielding from real collisions 14-4
14.4.2 Shielding from Proton and Antiproton Beams 14-4
14.5 Mixing Facility for Detector Gases 14-8
14.6 Heating, Ventilation, and Air Conditioning 14-9
14.6.1 Overview 14-9
14.6.2 Collision Hall Specification and Design 14-10
14.6.3 First Floor Counting Room Specification and Design 14-10
14.6.4 Second Floor Trigger & Control Room Design 14-11
14.6.5 Other General HVAC Issues 14-11

15 Publications **15-1**