The Mu2e Experiment

Tomo Miyashita
Caltech

On Behalf of the Mu2e Collaboration

CIPANP 2018
Palm Springs, CA
May 29th, 2018

This document was prepared by Mu2e collaboration using the resources of the Fermi National Accelerator Laboratory (Fermilab), a U.S. Department of Energy, Office of Science, HEP User Facility. Fermilab is managed by Fermi Research Alliance, LLC (FRA), acting under Contract No. DE-AC02-07CH11359.

Overview

- Motivation and Theory
- Experiment Overview
- Experiment Design
 - Proton Beam
 - Production and Stopping Targets
 - Tracker
 - Calorimeter
 - CRV
 - DAQ/Trigger
- Mu2e Schedule
- Mu2e II
- Summary

Motivation

- Mu2e is searching for Charged Lepton Flavor Violation (CLFV)
 - Specifically, the conversion of a μ^- to an e^- in the field of a nucleus:

- Using the current Fermilab accelerator complex, we intend to achieve a sensitivity 4 orders of magnitude better than current limits:

Target Sensitivity:

$$R_{\mu e} = \frac{\Gamma [\mu^- + A(Z, N) \rightarrow e^- + A(Z, N)]}{\Gamma [\mu^- + A(Z, N) \rightarrow \nu_\mu + A(Z - 1, N + 1)]} < 6.7 \times 10^{-17} (90\% \text{CL})$$

4 orders of magnitude better than current limits: SINDRUM II
[W. Bertl et al., Eur. Phys. J. C 47, 337-346 (2006)]

- We will have discovery sensitivity over a broad range of New Physics parameter space

Flavor Violation

- We have known for a long time that quarks mix $\Rightarrow$ (Quark) Flavor Violation
 - Mixing strengths parameterized by the CKM matrix
- We have known since 2001 that neutrinos can also mix $\Rightarrow$ (Neutral) Lepton Flavor Violation
 - Mixing strengths parameterized by the PMNS matrix
- Why not charged leptons as well?
 - Charged Lepton Flavor Violation (CLFV)

CLFV in the Standard Model

- CLFV is not technically allowed in the SM because since charged lepton number is accidentally conserved when neutrinos are massless
- However, if we include massive neutrinos in our model then CLFV becomes possible at the loop level due to neutrino oscillations:

- This process is extremely suppressed ($\mathcal{B}(\mu^- \rightarrow e^- \gamma) < 10^{-54}$)
- Therefore, any signal at our sensitivity would be a sign of new physics

Example CLFV Processes

- Potential channels for CLFV searches:

Process	Current Limit	Next Generation exp
$\tau \rightarrow \mu \eta$	$\text{BR} < 6.5 \times 10^{-8}$	$10^{-9} - 10^{-10}$ (Belle II)
$\tau \rightarrow \mu \gamma$	$\text{BR} < 6.8 \times 10^{-8}$	
$\tau \rightarrow \mu \mu \mu$	$\text{BR} < 3.2 \times 10^{-8}$	
$\tau \rightarrow e e e$	$\text{BR} < 3.6 \times 10^{-8}$	
$K_L \rightarrow e \mu$	$\text{BR} < 4.7 \times 10^{-12}$	
$K^+ \rightarrow \pi^+ e^- \mu^+$	$\text{BR} < 1.3 \times 10^{-11}$	
$B^0 \rightarrow e \mu$	$\text{BR} < 7.8 \times 10^{-8}$	
$B^+ \rightarrow K^+ e \mu$	$\text{BR} < 9.1 \times 10^{-8}$	
$\mu^+ \rightarrow e^+ \gamma$	$\text{BR} < 4.2 \times 10^{-13}$	10^{-14} (MEG Upgrade)
$\mu^+ \rightarrow e^+ e^+ e^-$	$\text{BR} < 1.0 \times 10^{-12}$	10^{-16} (Mu3e)
$\mu N \rightarrow e N$	$R_{\mu e} < 7.0 \times 10^{-13}$	10^{-17} (Mu2e, COMET)

- Although CLFV τ processes could have larger branching ratios than μ processes, dedicated muon experiments can produce $O(10^{10})$ μ /s whereas colliders produce $O(10^{10})$ τ /year

New Physics Reach

- There are many possible new physics contributions to $\mu N \rightarrow e N$, either through loops or the exchange of heavy intermediate particles
- Many NP models predict rates observable at next gen CLFV experiments

Loops

Supersymmetry

Heavy Neutrinos

Two Higgs Doublets

Contact Terms

Compositeness

Leptoquarks

New Heavy Bosons /
Anomalous Couplings

Model-Independent Effective Lagrangian

$$L_{\text{CLFV}} = \frac{m_m}{(1+k)\Lambda^2} \bar{m}_R s_{mn} e_L F^{mn} + \frac{k}{(1+k)\Lambda^2} \bar{m}_L g_m e_L (\bar{u}_L g_m u_L + \bar{d}_L g_m d_L) + h.c.$$

Λ : effective mass scale of New Physics

k : relative contribution of the contact term

“Dipole term”

- CLFV can probe very high mass scales $O(1000 - 10,000 \text{ TeV})$

Courtesy A. de Gouvea, B. Bernstein, D. Hitlin

“Contact term”

Motivation II

- Mu2e has discovery sensitivity across a wide range of models:

W. Altmannshofer, A.J.Buras, S.Gori, P.Paradisi, D.M.Straub

★★★★ = Discovery Sensitivity

	AC	RVV2	AKM	δ LL	FBMSSM	LHT	RS
$D^0 - \bar{D}^0$	★★★★	★	★	★	★	★★★★	?
ϵ_K	★	★★★★	★★★★	★	★	★★	★★★★
$S_{\psi\phi}$	★★★★	★★★★	★★★★	★	★	★★★★	★★★★
$S_{\phi K_S}$	★★★★	★★	★	★★★★	★★★★	★	?
$A_{CP}(B \rightarrow X_s \gamma)$	★	★	★	★★★★	★★★★	★	?
$A_{7,8}(B \rightarrow K^* \mu^+ \mu^-)$	★	★	★	★★★★	★★★★	★★	?
$A_9(B \rightarrow K^* \mu^+ \mu^-)$	★	★	★	★	★	★	?
$B \rightarrow K^{(*)} \nu \bar{\nu}$	★	★	★	★	★	★	★
$B_s \rightarrow \mu^+ \mu^-$	★★★★	★★★★	★★★★	★★★★	★★★★	★	★
$K^+ \rightarrow \pi^+ \nu \bar{\nu}$	★	★	★	★	★	★★★★	★★★★
$K_L \rightarrow \pi^0 \nu \bar{\nu}$	★	★	★	★	★	★★★★	★★★★
$\mu \rightarrow e \gamma$	★★★★	★★★★	★★★★	★★★★	★★★★	★★★★	★★★★
$\tau \rightarrow \mu \gamma$	★★★★	★★★★	★	★★★★	★★★★	★★★★	★★★★
$\mu + N \rightarrow e + N$	★★★★	★★★★	★★★★	★★★★	★★★★	★★★★	★★★★
d_n	★★★★	★★★★	★★★★	★★	★★★★	★	★★★★
d_e	★★★★	★★★★	★★	★	★★★★	★	★★★★
$(g-2)_\mu$	★★★★	★★★★	★★	★★★★	★★★★	★	?

Table 8: “DNA” of flavour physics effects for the most interesting observables in a selection of SUSY and non-SUSY models ★★★★★ signals large effects, ★★ visible but small effects and ★ implies that the given model does not predict sizable effects in that observable.

arXiv:0909.1333[hep-ph]

Experimental Concept

- Generate a beam of low momentum muons
 - Muons are stopped in an aluminum target
 - When stopped muons convert to electrons, the nucleus recoils and the electron is emitted at a specific energy
- Signal is mono-energetic electron at 104.9 MeV
 - Main background is Decay In Orbit (DIO) events
- To achieve our target sensitivity, we need $\sim 10^{18}$ stopped muons over 3 year run
 - $\Rightarrow \sim 10^{10}$ stopped muons per second

Decay In Orbit

Decay In Orbit Energy Distribution

- Although naively, the maximum electron energy from muon decay should be far below our signal energy (104.9 MeV)...

Decay In Orbit Energy Distribution

- Once you include the effect of the μ -Al²⁷ binding energy and radiative corrections...

Decay In Orbit Energy Distribution

- The maximum energy for the DIO electrons comes very close to the signal energy:

- Therefore, it is important that we have good energy resolution

Design Overview

- **Production Target + Production Solenoid**
 - High intensity, pulsed, 8 GeV proton beam strikes tungsten production target producing pions
 - Pions are captured by the graded magnetic field and decay to muons
- **Transport Solenoid**
 - Selects low momentum, negative muons
 - Absorbers and Collimators eliminate high energy negative particles, positive particles, and line-of-sight neutrals
- **Stopping Target, Detector, and Detector Solenoid**
 - Muons are stopped on an aluminum target
 - Tracker measures momentum and trajectories of from muonic atoms
 - Calorimeter measures energy/time
- **Cosmic Ray Veto detector surrounds detector solenoid**

The Mu2e Proton Beam

- Mu2e will take advantage of the existing Booster, Recycler, Accumulator, and Antiproton Source Debuncher rings at Fermilab
- Mu2e will run in parallel with NOvA

FERMILAB'S ACCELERATOR CHAIN

Proton Pulse Structure

- Proton Pulse Structure:

- We use a pulsed proton beam with a delayed data-taking window to suppress short-lived (prompt) backgrounds
- A 700 ns delay reduces pion background by $> 10^{-9}$

Production Target

- Production Target
 - Radiatively cooled tungsten target suspended by wires
 - Produces pions when struck by the proton beam
 - Pions are guided to the stopping target by the production and transport solenoids

Stopping Target

- Stopping Target
 - Aluminum stopping target composed of foils suspended by wires
 - If a signal is seen, other stopping target materials may be used to narrow down what kind of physics is responsible
 - Design is still being optimized, but it will probably consist of something like aluminum foil annuli suspended at intervals in a cylindrical volume

Tracker I

- A low-mass annular tracker provides us with high-precision measurements of charged particle momenta
- Designed to function in a high background environment
- Within the detector solenoid, track radius is proportional to energy so we use an annular design that only detects particles with large enough radii

- Expect $< 180 \text{ keV/c } p_T$ resolution at $105 \text{ MeV/c } (< 0.18\%)$

Tracker II

- Tracker Construction:

- Tracker is constructed from self-supporting **panels** of low mass straws tubes detectors:

- 5 mm diameter straw
- Spiral wound
- Walls: 12 mm Mylar + 3 mm epoxy + 200 Å Au + 500 Å Al
- 25 mm Au-plated W sense wire
- 33 – 117 cm in length
- 80/20 Ar/CO₂ with HV < 1500 V

96 straws/panel

- Sets of 6 panels are attached to form a **plane**, 2 planes are combined to form a **station**, and 18 stations are arranged in a cylindrical volume to form the tracker:

plane

6 panels/plane

station

2 panels/station

18 station tracker

Tracker III

- Tracker Construction:

Calorimeter I

- Calorimeter Serves to
 - Distinguish muons from electrons
 - Aid in track pattern recognition
 - Provide tracker-independent trigger
 - Provide accurate timing information for bkg rejection

- Calorimeter Design:

- Two annuli with radius 37-66 cm
- Disks separated by 70 cm ($1/2 \lambda$)
- ~674 CsI crystals per disk
- Two $14 \times 20 \text{ mm}^2$ six-element SiPMs / crystal
- Square crystals ($34 \times 34 \times 200 \text{ mm}^3$)

Calorimeter II

- Wrap crystals in Tyvek and stack in annulus
- A backplane assembly provides cooling and slots mounting crystal readout electronics
- Insert SiPM holders with front end electronics (FEE) into the backplane (air-gap coupling)
- FEE are read out by readout controllers housed in crates

Crystal Stacking

SiPM Holder

Calorimeter III

- The calorimeter will be calibrated using activated Fluorine-rich fluid
 - Fluorinert is activated using neutrons from a DT generator
 - Fluid is pumped through pipes in front of the disks
 - Calibrate energy scale to $< 0.5\%$ in a few minutes
- A UV laser system will continuously monitor SiPM gains
 - Distribute light using silica optical fibers

Prototype Spectrum

Calorimeter Prototype

Calorimeter Prototype Test Beam

- May 2017 test beam with 70-115 MeV electrons at INFN Frascati
 - 51 30x30x200 mm³ CsI crystals
 - Readout: Hamamatsu, SNESSL, and Advansid MPPCs
- Results:

ENERGY RESOLUTION

Calibration with e^- at 0°
For 100 MeV e^- at 50°:
Energy resolution $\sim 7\%$

TIME RESOLUTION

For 100 MeV e^- at 50°:
 Δt resolution $\sim 340 \text{ ps}$
Single sensor resolution $\sim 240 \text{ ps}$

Δt : Time difference between two sensors reading the same crystal.

- Energy and time resolutions are well within the requirements

Cosmic Ray Veto I

- The Cosmic Ray Veto (CRV) system surrounds the detector solenoid and half the transport solenoid
- CRV identifies cosmic ray muons

- Each day, ~ 1 conversion-like electron is produced by cosmic rays
- Need the CRV to suppress this background

Cosmic Ray Veto II

- The CRV is composed of 4 layers of overlapping panels of extruded polystyrene scintillator

- Each panel is composed of $5 \times 2 \times \sim 450 \text{ cm}^3$ scintillator bars
 - 2 embedded wavelength-shifting fibers per bar
 - Both ends of the bars are readout by SiPMs
 - In testing, the veto achieves $\varepsilon > 99.4\%$ per layer

DAQ/Trigger

- Data Acquisition (DAQ) system provides readout and control for all the detector subsystems

- Trigger processing is handled almost entirely in software (with some FPGA-based pre-processing)
 - Allows us to take advantage of commercial computing hardware
 - Filters designed and tested in the offline environment can be run in the online trigger environment

DAQ Server Setup

- Online processing provided by 40 commercial 3U rack-mount servers
- Each server houses 2 PCIe cards with onboard FPGA and custom firmware that provide detector readout/control as well as data pre-processing

Mu2e Building

The Mu2e Collaboration

Over 200 Scientists from 37 Institutions

Argonne National Laboratory • Boston University • Brookhaven National Laboratory • Lawrence Berkeley National Laboratory and University of California, Berkeley • University of California, Davis • University of California, Irvine • California Institute of Technology • City University of New York • Joint Institute for Nuclear Research, Dubna • Duke University • Fermi National Accelerator Laboratory • Laboratori Nazionali di Frascati • INFN Genova • Helmholtz-Zentrum Dresden-Rossendorf • University of Houston • Institute for High Energy Physics, Protvino • Kansas State University • INFN Lecce and Università del Salento • Lewis University • University of Liverpool • University College London • University of Louisville • University of Manchester • Laboratori Nazionali di Frascati and Università Marconi Roma • University of Minnesota • Institute for Nuclear Research, Moscow • Muons Inc. • Northern Illinois University • Northwestern University • Novosibirsk State University/Budker Institute of Nuclear Physics • INFN Pisa • Purdue University • University of South Alabama • Sun Yat Sen University • University of Virginia • University of Washington • Yale University

Detector Hall (Lower Level)

Mu2e Schedule

Z-Dependence of $\mu \rightarrow e$ Conversion

Mu2e II Introduction

- As Mu2e approaches commissioning, we are also looking toward future upgrades
- The proposed Mu2e II experiment aims to achieve an order of magnitude improvement in sensitivity over Mu2e
 - **If there is no signal at Mu2e:** We could extend our sensitivity to find a signal or set new limits
 - **If Mu2e does see something:** We can improve our statistical significance and use different target materials to narrow down the NP processes involved
- To achieve a 10X improvement, we need:
 - An upgraded proton source (already approved)
 - Other upgrades to parts of the detector
- We aim to reduce costs by reusing parts of mu2e wherever feasible

Mu2e II Plans

- So far, various studies of Mu2e II backgrounds, sensitivity, and radiation damage have been performed
- A series of Mu2e II workshops has been held and the collaboration is involved in the Fermilab PIP-II planning process (a superconducting linac for LBNF and the muon campus)
 - PIP-II will have an energy of 800 MeV (Mu2e's proton source is 8 GeV) which is below the anti-nucleon production threshold and will result in less background
- An expression of interest was recently submitted to the Fermilab PAC
- Timecale:
 - Mu2e is expected to run for 4 years of data-taking at full intensity
 - Assuming 2-3 years from the end of Mu2e to the start of Mu2e II, Mu2e II could begin taking data around 2030

Summary

- The Mu2e experiment will improve current $\mu^- N \rightarrow e^- N$ CLFV sensitivity limits by 4 orders of magnitude (and thereby constrain many NP models at mass scales up to $\sim 10,000$ TeV)
- Mu2e will be sensitive to a broad range of NP models
- If we see a signal, switching to another stopping target material will provide further information about the Lorentz structure of the NP
- Progress is on schedule and we plan to begin commissioning in 2020

Backup Slides

Purely Leptonic Conversion Processes

$$L_{\text{CLFV}} = \frac{m_m}{(1+k)\Lambda^2} \bar{m}_R s_m e_L F^{mn} + \frac{k}{(1+k)\Lambda^2} \bar{m}_L g_m e_L (\bar{e}_L g_m e_L) + h.c.$$

Λ : effective mass scale of New Physics k : relative contribution of the contact term