Charged Lepton Flavor Violation:

$$\mu^- N \rightarrow e^- N$$

and

$$\mu^- N \rightarrow e^+ N$$

R. Bernstein
Fermilab

COFI 2018
San Juan, Puerto Rico

This document was prepared by Mu2e collaboration using the resources of the Fermi National Accelerator Laboratory (Fermilab), a U.S. Department of Energy, Office of Science, HEP User Facility. Fermilab is managed by Fermi Research Alliance, LLC (FRA), acting under Contract No. DE-AC02-07CH11359.

Outline

- The search for muon-electron conversion:

$$\mu^- N \rightarrow e^- N$$

- Experimental Technique:

- Mu2e, COMET, DeeMe

- Mu2e-II

- Very preliminary comments on

$$\mu^- N \rightarrow e^+ N$$

What is Muon to Electron Conversion?

- Muon converts to an electron in the field of a nucleus:

$$R_{\mu e} = \frac{\Gamma(\mu^- + N(A, Z) \rightarrow e^- + N(A, Z))}{\Gamma(\mu^- + N(A, Z) \rightarrow \text{all muon captures})}$$

- Effectively zero Standard Model background
 - a signal is new physics
- Experiments to be discussed can measure a signal with SES of $\sim 3 \times 10^{-17}$, discovery at 2×10^{-16}
 - typical predictions for EWSB $\sim 10^{-15}$

How Small is Our SES?

- Pretty Rare: let us know if this happens to you!
You can immediately join the experiment

Probability of...	
rolling a 7 with two dice	1.67E-01
rolling a 12 with two dice	2.78E-02
getting 10 heads in a row flipping a coin	9.77E-04
drawing a royal flush (no wild cards)	1.54E-06
getting struck by lightning in one year in the US	2.00E-06
winning Pick-5	5.41E-08
winning MEGA-millions lottery (5 numbers+megaball)	3.86E-09
your house getting hit by a meteorite this year	2.28E-10
drawing two royal flushes in a row (fresh decks)	2.37E-12
your house getting hit by a meteorite today	6.24E-13
getting 53 heads in a row flipping a coin	1.11E-16
your house getting hit by a meteorite AND you being struck by lightning both within the next six months	1.14E-16
your house getting hit by a meteorite AND you being struck by lightning both within the next three months	2.85E-17

Neutrinos and Mu2e

- Neutrino Oscillations are the only Standard Model background (except neutrino oscillations are not in the Standard Model)

$$\text{BR}(\mu \rightarrow e \gamma) = \frac{3\alpha}{32\pi} \left| \sum_{i=2,3} U_{\mu i}^* U_{ei} \frac{\Delta m_{1i}^2}{M_W^2} \right|^2 < 10^{-54}$$

- nobody understood why $\mu \rightarrow e \gamma$ wasn't 10^{-4} until we hypothesized two neutrinos ($\nu_\mu \neq \nu_e$)
- linkage of CLFV to oscillations, see-saw, Majorana vs. Dirac are getting more interest

Contributions to μe Conversion

Supersymmetry

$$\text{rate} \sim 10^{-15}$$

Compositeness

$$\Lambda_c \sim 3000 \text{ TeV}$$

Leptoquark

$$M_{LQ} = 3000 (\lambda_{\mu d} \lambda_{e d})^{1/2} \text{ TeV}/c^2$$

Heavy Neutrinos

$$|U_{\mu N} U_{e N}|^2 \sim 8 \times 10^{-13}$$

Second Higgs Doublet

$$g(H_{\mu e}) \sim 10^{-4} g(H_{\mu \mu})$$

Heavy Z' Anomal. Z Coupling

$$M_{Z'} = 3000 \text{ TeV}/c^2$$

also see Flavour physics of leptons and dipole moments, [arXiv:0801.1826](https://arxiv.org/abs/0801.1826) ;

Marciano, Mori, and Roney, Ann. Rev. Nucl. Sci. 58, doi:[10.1146/annurev.nucl.58.110707.171126](https://doi.org/10.1146/annurev.nucl.58.110707.171126) ;

de Gouvea and Vogel, arXiv:1303.4097v2

Effective Lagrangian

$$\mathcal{L}_{\text{CLFV}} = \frac{m_\mu}{(\kappa + 1)\Lambda^2} \bar{\mu}_R \sigma_{\mu\nu} e_L F^{\mu\nu} + \frac{\kappa}{(1 + \kappa)\Lambda^2} \bar{\mu}_L \gamma_\mu e_L (\bar{u}_L \gamma_\mu u_L + \bar{d}_L \gamma_\mu d_L)$$

μe Conversion and $\mu \rightarrow e \gamma$

1) Mass Reach to $\sim 10^4$ TeV for unit coupling, x10 in mass scale for dim-6

2) Mu2e and MEG-II are complementary in loop-dominated physics.

3) These are discovery experiments

Mu2e, g-2, and $\mu \rightarrow e\gamma$

Yaguna,
hep-ph/0502014v2
MSSM w mSUGRA

- Need:

- observation of CLFV in more than one channel, and/or
- evidence from LHC, g-2, or elsewhere

to allow discrimination among different models

$$M_H = \sqrt{2} |\mu|$$

CLFV and the LHC

LHC inverse problem

Experimental Signal

$$\mu^- N \rightarrow e^- N$$

- A Single Mono-energetic Electron
 - muon falls into 1s state in “stopping target”
- Nucleus coherently recoils off outgoing electron
- If $N = \text{Al}$, $E_e \sim 105. \text{ MeV} \sim m_\mu$
 - electron energy depends on Z
 - physics in Z -dependence of rate

very low energies for
HEP!

Mu2e: x10,000 improvement

- World's most intense muon beam:
 - 10^{10} μ /sec at detector under construction
 - Superconducting solenoid system to form muon beam
 - Efficient muon collection; see $\sim 10^{18}$ muons
- Have to reduce backgrounds to take advantage of statistics
 - Pulsed Beam reduces a background
 - And a high-resolution spectrometer to make muon-related backgrounds small

Backgrounds and Design

	<i>source</i>	<i>scales with</i>	<i>solution</i>
Intrinsic Backgrounds	decay-in-orbit	# of muons	detector resolution
Beam	radiative pion capture	closeness to beam pulse	pulsed beam
Running Time	cosmic ray	live time	veto system

Decay-In-Orbit: usually not background

- Peak and Endpoint of free muon decay spectrum is at

$$E_{\text{max}} = \frac{m_{\mu}^2 + m_e^2}{2m_{\mu}} \approx 52.8 \text{ MeV}$$

- Detector will be insensitive to electrons at this energy
- Recall *signal* at $105 \text{ MeV} \gg 52.8 \text{ MeV}$

Michel=free muon decay

Decay-In-Orbit Background

- Same process as before
- But this time, include electron recoil off nucleus
- If neutrinos are at rest, **the DIO electron can be exactly at conversion energy** (up to neutrino mass)

Decay-In-Orbit Background

- Same process as before
- But this time, include electron recoil off nucleus
- If neutrinos are at rest, **the DIO electron can be exactly at conversion energy** (up to neutrino mass)

Decay-In-Orbit Background

- Same process as before
- But this time, include electron recoil off nucleus
- If neutrinos are at rest, **the DIO electron can be exactly at conversion energy** (up to neutrino mass)

Decay-in-Orbit Shape

Szafron 10.5506/APhysPolB.46.2279: Radiative Corrections

Czarnecki: 10.1016/j.physletb.2015.12.008 many other papers

Decay-in-Orbit Shape

Szafron 10.5506/APhysPolB.46.2279: Radiative Corrections

Czarnecki: 10.1016/j.physletb.2015.12.008 many other papers

Backgrounds and Design

	<i>source</i>	<i>scales with</i>	<i>solution</i>
Intrinsic Backgrounds	decay-in-orbit	# of muons	detector resolution
Beam	radiative pion capture	closeness to beam pulse	pulsed beam
Running Time	cosmic ray	live time	veto system

Radiative Pion Capture

- Need π 's to make μ 's
- Sometimes those π 's live long enough to make it to the stopping target
- They can then undergo radiative pion capture (RPC):
 - $\pi N \rightarrow \gamma N'$ and the γ converts in the Al.
 - $\pi N \rightarrow \gamma N'$ and the γ internally converts
- Sometimes the e^- is at the signal energy

Prompt Backgrounds and Pulsed Beam

Al target foils: muon converts here

= muons, electrons, pions

Radiative Pion
Capture:

$$\pi N \rightarrow \gamma N$$

$\gamma \rightarrow e^+ e^-$ in foils

pulsed beam lets us
wait (1) until after
beam flash, and (2)
RPC background
decays away

Prompt Backgrounds and Pulsed Beam

Al target foils: muon converts here

= muons, electrons, pions

Radiative Pion
Capture:

$$\pi N \rightarrow \gamma N$$

$$\gamma \rightarrow e^+ e^- \text{ in foils}$$

pulsed beam lets us
wait (1) until after
beam flash, and (2)
RPC background
decays away

Prompt Backgrounds and Pulsed Beam

Al target foils: muon converts here

= muons, electrons, pions

Radiative Pion Capture:

$$\pi N \rightarrow \gamma N$$

$$\gamma \rightarrow e^+ e^- \text{ in foils}$$

pulsed beam lets us wait (1) until after beam flash, and (2) RPC background decays away

Prompt Backgrounds and Pulsed Beam

Al target foils: muon converts here

= muons, electrons, pions

Radiative Pion
Capture:

$$\pi N \rightarrow \gamma N$$

$\gamma \rightarrow e^+ e^-$ in foils

pulsed beam lets us
wait (1) until after
beam flash, and (2)
RPC background
decays away

Prompt Backgrounds and Pulsed Beam

Al target foils: muon converts here

= muons, electrons, pions

Radiative Pion Capture:

$$\pi N \rightarrow \gamma N$$

$\gamma \rightarrow e^+ e^-$ in foils

pulsed beam lets us wait (1) until after beam flash, and (2) RPC background decays away

Prompt Backgrounds and Pulsed Beam

Al target foils: muon converts here

= muons, electrons, pions

Radiative Pion Capture:

$$\pi N \rightarrow \gamma N$$

$$\gamma \rightarrow e^+ e^- \text{ in foils}$$

pulsed beam lets us wait (1) until after beam flash, and (2) RPC background decays away

Prompt Backgrounds and Pulsed Beam

Al target foils: muon converts here

= muons, electrons, pions

Radiative Pion Capture:

$$\pi N \rightarrow \gamma N$$

$$\gamma \rightarrow e^+ e^- \text{ in foils}$$

pulsed beam lets us wait (1) until after beam flash, and (2) RPC background decays away

Prompt Backgrounds and Pulsed Beam

Al target foils: muon converts here

= muons, electrons, pions

Radiative Pion Capture:

$$\pi N \rightarrow \gamma N$$

$$\gamma \rightarrow e^+ e^- \text{ in foils}$$

pulsed beam lets us wait (1) until after beam flash, and (2) RPC background decays away

Prompt Backgrounds and Pulsed Beam

Al target foils: muon converts here

= muons, electrons, pions

Radiative Pion Capture:

$$\pi N \rightarrow \gamma N$$

$$\gamma \rightarrow e^+ e^- \text{ in foils}$$

pulsed beam lets us wait (1) until after beam flash, and (2) RPC background decays away

Prompt Backgrounds and Pulsed Beam

Al target foils: muon converts here

= muons, electrons, pions

Radiative Pion Capture:

$$\pi N \rightarrow \gamma N$$

$$\gamma \rightarrow e^+ e^- \text{ in foils}$$

now μ is only source of
105 MeV electron

pulsed beam lets us
wait (1) until after
beam flash, and (2)
RPC background
decays away

SINDRUM-II Results

- Effectively constant beam
 - 51 MHz (**~20 nsec**) repetition rate, ~0.3 nsec pulse
- Small time separation between signal and prompt pion backgrounds
 - bottom plot is first half of **20 nsec**, top plot is 2nd half
 - delay lowers background

$$B_{\mu e}^{\text{Au}} < 7 \times 10^{-13} \text{ @ 90\% CL}$$

Pulsed Beam Structure

π backgrounds

signal window

- Wait out pion backgrounds, then open signal window
- Can't “restart the clock” with out-of-pulse protons
- Need 10^{-10} in-pulse/out-of-pulse ratio (**extinction**)
 - will measure and monitor during experiment

Pulsed Beam Structure

π backgrounds

signal window

- Wait out pion backgrounds, then open signal window
- Can't “restart the clock” with out-of-pulse protons
- Need 10^{-10} in-pulse/out-of-pulse ratio (**extinction**)
 - will measure and monitor during experiment

Pulsed vs. “Steady” Beam

- Decay expts, $\mu \rightarrow e\gamma$ and $\mu \rightarrow eee$ want a steady beam: PSI
- need to minimize backgrounds from coincidences of two decays
- $(\text{Rate})^2$ bkg vs $\text{Rate}(\text{signal})$
- muon-electron conversion wants a pulsed beam: FNAL/J-PARC
- Many pion-induced backgrounds after proton pulse
- Take advantage of 26 nsec lifetime to “wait it out”

DC optimizes in rate

R. Bernstein (FNAL)

Pulsed optimizes
in time

COFI 2018

Beam Flash

- After proton beam strikes target, “flash” of photons and electrons, and many electrons hit stopping target and detector
- Large neutron flux as well that would deaden detectors
- By waiting:
 - activity from beam flash is over
 - And pion backgrounds have decayed by $\sim 10^{11}$
- This early flash has implications for Mu2e and especially for potential upgrades

Actual Experiments: Mu2e/COMET

mu2e.fnal.gov

4.6T $\longrightarrow$ B-field gradient $\longrightarrow$ 1T

Mu2e

Production

Transport

Detector

- Target protons at 8 GeV inside superconducting solenoid at 8kW: shielding a challenge
- Capture muons and guide through S-shaped region to Al stopping target

Detector Layout

finding electron track and momentum determination: highest precision, needed to reject decay-in-orbit

tracker

beam stop

stopping
target

calorimeter

- 1) PID separation of $\pi/\mu/e$
- 2) Seed for Track Finder
- 3) Standalone Trigger

Why Annular?

- Reduces beam activity and a background
 - don't want initial “flash” of activity from proton pulse, or remnant muon beam in detector (only $\sim 1/2$ of muon beam stops in target)
 - eliminates all but a tiny number of decay-in-orbit background
 - $p \sin\theta \sim qBR$ in solenoid, Michel e^- at small radius
 - so we're not rejecting 10^{18} ; only $\sim 10^5$ even reconstructed
- COMET uses a different method; not annular
 - advantages and disadvantages

Straw Tube Tracker

- 15 microns of Kapton (human hair = 10–80 microns)
- ~1 meter long straws, 5 mm diameter with a central gold-plated tungsten wire
- ~20,000 straws in a vacuum of 10^{-4} Torr

Calorimeter

- Two CsI crystal disks
 - hole, as in tracker, for passage of muon beam
 - distance chosen such that if signal electron goes down hole, hits next disk

“module 0”:
51 crystals

Backgrounds and Design

	<i>source</i>	<i>scales with</i>	<i>solution</i>
Intrinsic Backgrounds	decay-in-orbit	# of muons	detector resolution
Beam	radiative pion capture	closeness to beam pulse	pulsed beam
Running Time	cosmic ray	live time	veto system

Cosmic Ray Background

- At 10^{-17} there's a lot of rare backgrounds; here's one that is surprising but not too rare: 1/day!

- the experiment needs a 99.99% efficient veto (3/4 layers)
- in an environment with 10^{10} neutrons/cm²/sec from proton pulse

CR Veto Details

Neutron Rates

- Veto systems are never totally hermetic
 - even with 26 km of veto counters, area of a large house ($\sim 3000 \text{ ft}^2$) (extrusions completed)
- Simulated 250 experiment live-times in targeted regions

targeted simulations here, for example

Tracker/Calorimeter/ CRV Test Beam Results

- Energy and time response of 3X3 CsI crystal array
- PE yields of CRV scintillation counters read out by SiPMs
- Tracker Resolution measured and modeled at level of charge cluster formation
- *Measured resolutions and properties in the simulations*

arXiv: 1709.06587, submitted to NIM

DOI: 10.1088/1748-0221/12/05/P05007

Beam Under Construction

diagnostic absorber near g-2/Mu2e split:
is the beam as expected and does the
extinction work?

checking polarity now!
(before we turn on)

Mu2e Solenoid

Coil modules at ASG

R. Bernstein (FNAL)

~1 of 75
km of
cable and
spares
(cable
complete)

B4

at General Atomics
splice between solenoids

COFI 2018

Beginning Production

- Ramping up production and cold tests

~204 scientists
from
US, Italy, Russia,
Germany

production solenoid here

transport solenoid here

Mu2e Expected

90% CL $\sim 8 \times 10^{-17}$

$5\sigma \sim 2 \times 10^{-16}$

x10000 better than SINDRUM-II

Mu2e

typical SUSY at 10^{-15} : 40 events vs 0.4 bkg

Background Estimates

Process	Expected Number
Cosmic Ray Muons	0.25 ± 0.026
DIO	0.14 ± 0.09
RPC	0.025 ± 0.003
Antiprotons	0.047 ± 0.024
Muon DIF	< 0.003
Pion DIF	$0.001 \pm < 0.001$
Beam Electrons	$< 5 \times 10^{-4}$
Total	0.46 ± 0.03

Mu2e Schedule

Construction underway now;
setting up factories

COMET

- Stage I: (2021)
 - x100 better than SINDRUM-II
- Stage II
 - x10,000 better
 - same reach as Mu2e
- Important differences:
 - C- vs S- for transport
 - 2nd bend in detector solenoid

COMET

- Stage I: (2021)
 - x100 better than SINDRUM-II
- Stage II
 - x10,000 better
 - same reach as Mu2e
- Important differences:
 - C- vs S- for transport
 - 2nd bend in detector solenoid

COMET Progress

Chen Wu, Tau 2016
and
Y. Kuno, priv. comm

- Extinction measured $\sim 10^{-11}$
- Prototype Target
- Coil winding for capture solenoid
- Transport Solenoid in Hall
- 14 Coils of Detector Solenoid wound

Al stabilized SC wire

Coil winding

COMET Remaining

- Production Solenoid cable procured, but one has to then design a solenoid shielding system that will withstand heat and radiation
 - dumping up to 56 kW (Stage II) in a superconducting solenoid
 - design still underway
 - then needs construction
- Negotiation over running time with T2K
 - ~150 days live-time needed for Stage 1 (x100 improvement)
- Available schedules out-of-date, but Stage 1 ~ 2021

http://j-parc.jp/researcher/Hadron/en/pac_1707/PAC24thMinutes_final_draft.pdf

DeeMe

- DeeMe at J-PARC $\mu N \rightarrow e N$ with a 2×10^{-14} SES, x10 improvement
- **production target and conversion target are the same: not like Mu2e or COMET**

Calibration Spectra (μ^+ data)

DeeMe HV Switching

- Since the detector is so “close” to the production target, the detector has to be turned off near the beam flash
- HV switching on a MWPC

HV-Switching MWPC

Cathode Plane

3 mm

0.7 mm

3 mm

Anode Wire

Potential Wire

Rate

live window

t

Voltage

OFF ON OFF ...

Potential wire switching

t

- Expected detector rate
 - Prompt burst: 70 GHz/mm²
 - Delayed e⁻ signal or μ-e conversion
- Turn-off only during the prompt burst
 - Development has completed.
 - Four MWPCs already fabricated.
 - All read-out circuits including amp., digitizer are ready.

PTEP

Prog. Theor. Exp. Phys. 2017, 023C01 (11 pages)
DOI: 10.1093/ptep/ptw195

A fast high-voltage switching multiwire proportional chamber

IL Natori^{1,*}, N. Teshima², M. Aoki², H. Nishiguchi³, T. D. Nguyen², Y. Takezaki², Y. Furuya², S. Ito^{2,4}, S. Mihara⁵, D. Nagai⁶, Y. Nakatsugawa⁶, T. M. Nguyen², Y. Senyo², K. Shimizu², and K. Yamamoto²

¹High Energy Accelerator Research Organization (KEK), Beam-305-050, Japan
²Osaka City University, Goshu 328-8583, Japan
³Osaka University, Goshu 560-0043, Japan
⁴Present Address: Institute for Basic Science (IBS), Daejeon 305-380, Republic of Korea
⁵Present Address: Obayashi University, Okazaki 760-8556, Japan
⁶Present Address: Institute of High Energy Physics (IHEP), Beijing 100049, China
^{*}E-mail: natori@hep.kek.jp

Received October 21, 2016; Revised December 12, 2016; Accepted December 26, 2016; Published February 14, 2017

Next Talk by N. Teshima

DeeMe Status

- Depends on J-PARC H-line construction (different from COMET, DeeMe in Materials Science section)

Summary

- There is a competitive merit of physics in searching for μ -e conversion at sensitivity of 10^{-14} in timely manner.
- **It is important to maximize the potential of major discovery at J-PARC.**
- DeeMe, yet another mu-e conversion search with totally different method from COMET and Mu2e, creates harmonious diversity for J-PARC.
- DeeMe has already acquired **Stage-2 Approval from muon-PAC of KEK/IMSS.**
- Construction of **detector system has completed** with Grant-in-Aid for Scientific Research of Japan (Basic Science S, 2012–2016).
- An **integration test of the whole detector system** including DAQ had **successfully** performed. A **DIO measurement** had done at the same time, and analysis is ongoing.
- The **Detector system is ready** for the physics data taking.
- We are hoping to start soon after the completion of the beamline construction. No beam-time conflicts with T2K, KOTO or whatever the physics programs with the main ring of J-PARC.
- Meanwhile, we are keeping collaboration activities with detector improvements and by-product research.

Mu2e and COMET: High-Level Differences

- COMET Staging has obvious advantages for learning as you go
- Charge Symmetry of Detector:
 - Mu2e: charge symmetric, e^+e^- the same
 - 2nd Bend in COMET Stage II momentum selects ~ 105 MeV e^- only
 - Mu2e needs hole, COMET does not

Effect of Charge-Symmetry Choice

- Backgrounds
 - many background sources of e^- (RPC!) produce equal e^+e^-
 - Mu2e can measure them with e^+ *in situ*
 - *look “inside the box”, no blinding needed since e^+*
- Physics (next topic)
 - Mu2e can simultaneously measure $\mu^- N \rightarrow e^+ N'$, different/unique physics
 - COMET would have to reverse field, not trivial: separate runs

$$\mu^- N \rightarrow e^+ N^*$$

- Closely related to $\theta_{\nu 2\beta}$
 - or a leptoquark (not shown), ...

- <https://doi.org/10.1103/PhysRevD.95.115010>, <https://arxiv.org/pdf/1611.00032.pdf>, <https://arxiv.org/pdf/1705.07464.pdf>, Geib et al., Physics Letters B 764 (2017) 157–162 or <https://arxiv.org/abs/1609.09088> discusses relation to $\theta_{\nu 2\beta}$

$\mu^- N \rightarrow e^+ N^*$ Changes Nucleus

- The final state nucleus is different by $\Delta Z = 2$
 - different from muon-to-electron conversion, which is coherent and gets a Z^2 enhancement

One-Slide Summary

- Large Background from a physics process with the same μ^- we use for $\mu^- N \rightarrow e^- N$, called radiative muon capture
 - Probably need to look for GS→GS Transitions between initial, final state nuclei. Numerically, transitions to ground state not well known
 - Probably Al is not the best, need higher Z material like Ti, but that is natural direction for Mu2e anyway
- These are not “show-stoppers”. Work underway.

$$\mu^- N \rightarrow e^+ N^*$$
$$\text{GS} \rightarrow \text{GS in Mu2e}$$

- mono-energetic positron at known energy If B is binding energy, R recoil (# for ^{27}Al to ^{27}Na)

$$\begin{aligned} E_{\mu^- e^+} &= m_\mu + M(A, Z) - [M(A, Z - 2) + 2m_e - B_\mu - R(A)] \\ &= 92.31 \text{ MeV} \end{aligned}$$

- Mu2e acceptance at 92 MeV/c is relatively low; may need to turn down field, implying special run

Modeling $\mu^- N \rightarrow e^+ N^*$

Geib et al.

Physics Letters B 764 (2017) 157–162
and EXFOR database

- Usually imagine two possibilities:
 - transition to ground state
 - narrow
 - transition to giant dipole resonance (GDR)
 - very broad, 20 MeV $\rightarrow$ hard to do
 - and then since fraction to each not well known, quote separate limits

Calculating Signal: GS Transition Rate

- Ground State transitions are mono-energetic so can pick out positron.
- Last estimate:
 - P.C. Divari et al. / Nuclear Physics A 703 (2002) 409–431
 - Estimate 41% to GS; much larger than closure approximation estimates of GS rate

Background Processes

- Two that are relevant, and present different problems:
 - $\pi^- N \rightarrow \gamma N$ (Radiative Pion Capture = RPC)
 - $\mu^- N \rightarrow \gamma N$ (Radiative Muon Capture = RMC)
- The γ can convert either in the stopping target or undergo internal conversion (happen to be $\sim$ the same in Mu2e and COMET by coincidence).
 - RPC suppressed already, but RMC can't be: from μ^-
 - background e^+ for $\mu^- N \rightarrow e^+ N^*$

Calculating RMC Background: Closure Approximation

- Model transitions from an initial state to a single final state with a mean energy $\tilde{E}$ which is now a parameter
- So we also have a parameter k_{max} in the closure approximation
 - the biggest it could be is the kinematic limit from mass, recoil, and binding energy
 $\sim 101.865 \text{ MeV}/c^2$ in Al

RMC Spectrum

- Theory: use the closure approximation to derive $N(x) \propto (1 - 2x + 2x^2) \times (1-x)^2$ where $x = k/k_{max}$

- Data?

P. Christillin, Ref Th 2697, CERN

RMC Data

- How reliable is the closure approximation?
- Is there a tail?
- Can we minimize these uncertainties?
 - have signal region near endpoint of RMC spectrum

RMC vs Signal

- From Yeo et al. <https://arxiv.org/pdf/1705.07464.pdf>

FIG. 1. Fitting result of the energy distribution of the $\mu^- - e^+$ signal (short dashed red line) stacked on the on-shell RMC photon background (long dashed blue line) from ^{27}Al muon-stopping target when $Br(\mu^- - e^+) = 1.7 \times 10^{-12}$ and $N_{\mu\text{-stop}} = 10^{18}$. Black dots are pseudo data of positrons generated by the background and signal composite model.

kinematic k_{max} ;

just to indicate how much better
you do at higher Z

Mu2e is working on making these plots in our simulations

$\mu^- N \rightarrow e^+ N^*$ on Ti: Real Data

- SINDRUM actually used much older data on Ca to transfer to Ti
- Can't do better without measuring RMC and RPC
- Mu2e Simulations underway

Fig. 2. Positron momentum distributions for measuring periods with (a,b) and without (c) muon beam. The measured distribution in part a is compared with the *GS* and *GDR* expectations for $\mu^- \rightarrow e^+$ conversion. The insert b shows the distribution of ϕ_{rf} , the decay time relative to the 50.63 MHz cyclotron frequency, exhibiting a peak caused by misidentified scattered beam electrons. The events from the grey region outside the peak have been interpreted as *RMC* events. Their momentum distribution is compared with the results from the *RMC* simulation discussed in the text.

Current Limits

- From SINDRUM-II, to ground state and GDR at 90% CL
 - other materials, just quoting Ti

$\mu^- + Ti \rightarrow e^+ Ca$	$BR < 1.7 \times 10^{-12}$
$\mu^- + Ti \rightarrow e^+ Ca^*$	$BR < 3.6 \times 10^{-11}$

Which Material?

- Don't want $k_{max, kinematic} > E_{e^+(GS)}$ to the extent possible

	rate > 57 MeV/ OMC	k _{max}	k _{max} , kinematic	conversion energy
²⁷ Al	$1.43 \pm 0.13 \times 10^{-5}$	90.0 ± 2.0	101.9	92.4
²⁸ Si	$1.31 \pm 0.15 \times 10^{-5}$	89.4 ± 1.8	99.8	97.4
⁴⁸ Ti	$1.31 \pm 0.15 \times 10^{-5}$	89.2 ± 2.0	99.7	98.9

- Al not best choice? Ti (or Si with active target) might be much better; Ti also good for $\mu^- N \rightarrow e^- N$ (later)

COMET and $\mu^- N \rightarrow e^+ N^*$

- 105 MeV conversion electron from $\mu^- N \rightarrow e^- N$
- e^+ follows opposite path
- have to reverse dipole portion of field in second section, so separate run is required

perhaps OK in Stage 1 where detector charge-symmetric

COMET and $\mu^- N \rightarrow e^+ N^*$

- 105 MeV conversion electron from $\mu^- N \rightarrow e^- N$
- e^+ follows opposite path
- have to reverse dipole portion of field in second section, so separate run is required

perhaps OK in Stage 1 where detector charge-symmetric

Mu2e Summary

- $\mu^- Al \rightarrow e^- Al$
 - SES $\sim 3 \times 10^{-17}$
 - 90% CL $\sim 8 \times 10^{-17}$
 - 5σ discovery $\sim 2 \times 10^{-16}$
 - Run for 3 years; physics data starting 2022
- Upgrades in intensity and changes in material already under examination

Mu2e Upgrades

- Next Step in cLFV Program:

Upgrades and Z-Dependence

- Different Operators have different Z-dependence
 - Combine depending on the particular model
- Z penguins
- γ penguins
- dipole
- scalar

Lepton flavor violating mu - e conversion rate for various nuclei
M. Koike et al., J.Phys. G29 (2003) 2051-2054
DOI: [10.1088/0954-3899/29/8/401](https://doi.org/10.1088/0954-3899/29/8/401)

Relationship to Neutrinos (aka neutral leptons)

- want as high a Z as possible

V. Cirigliano, B. Grinstein, G. Isidori, M. Wise
Nucl.Phys.B728:121-134,2005

Choice of Z for Upgrade

- What Sets Material Choice? Lifetime:

$$\tau_{\mu}(\text{Al}) = 864 \text{ ns}$$

$$\tau_{\mu}(\text{Ti}) = 338 \text{ ns}$$

$$\tau_{\mu}(\text{Au}) = 74 \text{ ns}$$

Mu2e Upgrades

- Studies for x10 improvement with Ti look promising and will be continued; EOI written (1307.1168 and EOI at 1802.02599)
- We need detector and solenoid improvements
 - may need new production solenoid to handle lower energy beam and higher power.
- FNAL PIP-II natural for both pulsed and non-pulsed CLFV, could do $\mu^- N \rightarrow e^\pm N$, $\mu \rightarrow e \gamma$, $\mu \rightarrow 3e$, $\mu^- e^- \rightarrow e^- e^-$ at one facility

Advertisement

- 3rd International Conference on Charged Lepton Flavor Violation
 - we cover everything in CLFV: μ , τ , B , talks split between theory and experiment
 - three days, plenary only (w/posters)
 - 17-19 June 2019 at Kyushu U.
- For examples:
 - <http://clfv2013.le.infn.it> (referenced by Emilie P.)
 - <https://indico.fnal.gov/event/11128/> (Julian H.)

Conclusions

- Mu2e will:
 - Reduce the limit for $R_{\mu e}$ by more than four orders of magnitude, x10 in mass reach ($R_{\mu e} < 8 \times 10^{-17}$ @ 90% C.L.)
 - Discover unambiguous proof of new physics or
 - Set powerful constraints on a wide variety of models
- Mu2e will therefore both complement LHC results and independently probe up to 10^4 TeV/c²
- COMET and DeeMe in progress
- Upgrades already under consideration with a new muon CLFV program being mapped out