



# First field quality measurements of a 15 T Nb<sub>3</sub>Sn Dipole Demonstrator

September 24, 2019

Thomas Strauss, E. Barzi, J. DiMarco, V.V. Kashikhin, I. Novitski, M.  
Tartaglia, G. Velez, A.V. Zlobin

US Magnet Development Program


This manuscript has been authored by Fermi Research Alliance, LLC under Contract No. DE-AC02-07CH11359 with the U.S. Department of Energy, Office of Science, Office of High Energy Physics.

- **Data collection**
  - **Magnetic Measurement System**
  - **Measurement sensitivity**
  - **Centering Corrections**
- **Measurement discussion**
  - **Transfer Function (magnitude of the field)**
  - **Loop (Dynamic effects, eddy current)**
  - **Z-scan (behavior along magnet length)**
  - **Harmonics from Stair Step (geometric harmonics)**
  - **Comparison with Simulation**
  - **Decay and Snapback**
- **Summary**



# Magnetic Measurement System

- Rotating Coil Measurement System at Fermilab Vertical Magnet Test Facility
  - 0.75 – 1 Hz rotation
  - $R_{\text{ref}}$  set to 17 mm (56% of aperture)
- Shaft with attached probe to scan ‘warm bore’ of the magnet, 3 m stroke
- Two probes, offset by 130 mm (16 layers, 2 Loops, 13 Windings each)
  - 130 mm x 22.25 mm PCB probe
  - 26 mm x 22.25 mm PCB probe
  - Dipole bucked signal





# 26 mm Probe sensitivity


130 mm probe sensitivity similar

Probe sensitivity  $b_n$  vs  $n$  (26 mm probe)



● 1500 A Stair step ● 2000 A Stair Step ● 4000 A Stair Step  
● 6000 A Stair Step ● 8000 A Stair Step ● 9000 A Stair Step

Probe sensitivity  $a_n$  vs  $n$  (26mm probe)



● 1500 A Stair step ● 2000 A Stair Step ● 4000 A Stair Step  
● 6000 A Stair Step ● 8000 A Stair Step ● 9000 A Stair Step


Sensitive to  $\sim n=7$

$$B_y + iB_x = B_1 10^{-4} \sum_{n=1}^{\infty} (b_n + ia_n) \left( \frac{x + iy}{R_{ref}} \right)^{n-1}$$




## Centering Correction


Higher order units versus current



Hysteresis feed-down from  $b_3$




# Transfer Function for multiple measurements




Conductor uses 11 mm width stainless core (nearly full width of cable)

## TF vs current for varying ramp rates




# Loop harmonic $b_3$ vs current for various ramp rates






## 20 A/s Loop measurements normal harmonics

$b_3, b_5, b_7$  and  $b_9$  vs current for Loop measurements




$a_3, a_5, a_7$  and  $a_9$  vs current for Loop measurements




## Z scan TF along magnet bore

Measured at 9kA




Measured at 9kA

Variations due to end field contributions  
z scan TF along center axis



## Z scan harmonics


Measured at 9kA, 26 mm probe



Errors smaller than symbols

## Z scan harmonics

Measured at 9kA



- $a_3$  depends on z-axis (possible misalignment), and value in center is consistent with loop and stair case measurements
- Oscillatory pattern likely due to cable transposition pitch (~12 cm)

Errors smaller than symbols




Geometric harmonics nearly identical in stair step and loop, small except for a2,a3,b2, and b3

- Stair step, 26 mm probe**

current	B main	TF	b2	b3	b4	b5	b6	b7	b8	b9		a2	a3	a4	a5	a6	a7	a8	a9
7003	10.599	1.514	1.4	-7.4	-0.9	0.1	-0.1	1.3	0.1	0.1		-1.3	-3.4	0.6	0.1	0.1	0.0	0.0	0.0

- Loop, 20 A/s, both probes, 130 mm offset in between**


Loop 20 A/s 26 mm																			
6996	1.512	1.4	-7.6	-1.0	0.2	-0.2	1.4	0.1	-0.2			-1.4	-3.7	0.8	0.2	0.2	0.1	0.0	0.0
Loop 20 A/s 130 mm																			
6996.030	1.514	-1.2	-7.2	-1.8	-1.3	-0.1	0.7	0.2	0.0			-1.5	-3.0	2.4	1.2	0.1	0.1	-0.1	0.0




Harmonics averaged from up and down ramp

Deuterium probe was loaned to FNAL by GMW


## MDPCT1 TF vs current



## $b_3$ versus dipole field




## $b_5$ versus dipole field



# Decay and Snapback

100 A reset current  
760 A plateau for 15 min  
10 A/s


$b_3$  versus time



# Snapback

100 A reset current  
760 A plateau for 15 min  
10 A/s

$b_3$  versus time






- Magnet  $TF$  and low-order field harmonics were measured using 26 mm and 130 mm long rotating coils in the field range up to  $\sim 14$  T.
- The measurements included geometrical components and contributions from the coil magnetization and iron yoke saturation effects.
- All the measured geometrical harmonics, except for  $a_2$ ,  $a_3$ ,  $b_2$ ,  $b_3$ , are small, on the level of 1 unit or less at  $R_{\text{ref}}=17$  mm.
- The coil magnetization effect in MDPCT1 at low fields is large due to the high critical current density and relatively large sub-element size in the contemporary  $\text{Nb}_3\text{Sn}$  strands.
- The iron yoke saturation effect in MDPCT1 starts at fields above 2.5 T and is also large.
- Both coil magnetization and iron saturation effects are in good agreement with theoretical predictions for  $TF$  and  $b_3$
- The eddy current effect in the cable on the  $TF$  and field harmonics in MDPCT1 was suppressed by using a stainless-steel core inside the cables
- A first glimpse at Decay and snapback showed no new surprises assuming an LHC type accelerator profile

- We thank the technical staff of FNAL APS-TD for contributions to magnet design, fabrication and test, and US-MDP Management Group and Technical Advisory Committee for the support of this project.
- We thank GMW ([www.gmw.com](http://www.gmw.com)) for providing us with a Metrolab 1226 8-22T NMR probe for our PT2026 Teslameter


# 130 mm Probe sensitivity

Probe sensitivity  $b_n$  vs  $n$  (130 mm probe)



● 1500 A Stair step ● 2000 A Stair Step ● 4000 A Stair Step  
● 6000 A Stair Step ● 8000 A Stair Step ● 9000 A Stair Step

Probe sensitivity  $a_n$  vs  $n$  (130 mm probe)



× 1500 A Stair step × 2000 A Stair Step ● 4000 A Stair Step  
+ 6000 A Stair Step - 8000 A Stair Step - 9000 A Stair Step

Sensitive to  $\sim n=8$